

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

产品规格

Date

Mon Oct 30 2023

Eaton Bussmann series high speed square body fuse

170M3359

051712255721

78 mm

123 mm

155 mm

705 g

RoHS Compliant EAC CE

IEC 60269-4 UL 248-13

200 kAIC

76 mm

No

AC

50 A

French style EKN/Type K Indicator for Micro

Other

Type K Indicator for micro

1\*

690 V

Centre fuse status indicator

515 at 660 V

None

M8

aR (accompanied semiconductor protection)

11 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

77

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard